



Technical data

- 1.Nominal voltage: 150V/5A
PITCH:2.54mm
- 2.Connection capacity:
AWG 26-20
- 3.Insulation Withstanding Voltage:
AC 1300V/MIN
- 4.Insulation Resistance:
1000MΩ or more at DC500V
- 5.Stripping length: 7-8mm
- 6.Using temperature range:-40C° -15C°

7.Undimensioned Tolerances:

Dim L=(P-1)×2.54+3.1	Dim B	Dim L
Dim B=(P-1)×2.54	±0.15	±0.20
P = 1/2 Number of poles(04-48)	over 30mm-60mm ±0.20	±0.25
	over 60mm-90mm ±0.30	±0.30
	over 90mm ±0.30	±0.40

8.Safety approval:

- 9.RoHS Compliance
- 10.Critical dimension:

- PDFD254 XXX XXX
- ① Poles 2x2P-2x24P
- ② Color
- 0 Black 5 Green 6 Blue G Plae grey....
- ③ Custom
- 000 K MARK 00K KUNACON MARK

6	FLANGE SCREW	STEEL	M2.0, Zn PLATED	2
5	WIRE GUARD	Stainless steel	t=0.25mm	P
4	CONTACT	BRONZE (PbBz)	t=0.3mm TIN PLATED	P
3	LEVEL	POM UL94HB	ORANGE	P
2	COVER	PA66 UL94V-0	ALL COLOR	1
1	BODY	PA66 UL94V-0	ALL COLOR	1

DWG. WF. Zhang		DATE	2020.08.27	MM	SHEET:	1 OF 1	Tolerance
CHK. WF. Zhang		DATE	2020.08.27	SCALE:	NONE 3:1 (.)		REV: A1
APP.	DATE						
TITLE:		PD-FD254 Series Double row					
PART NO.		PDFD254XXXXXX					
DWG NO.		PD-F254-B001					

REV	SIGN	DESCRIPTION	CHK.	DATE



KUNA Contact Technology Co. Ltd
http://www.kunacon.com